

Platinum

**BREATHABLE EXTRA WHITE
WATER-REPELLENT
AND MOULD-RESISTANT PAINT
WITH HIGH COVERING ABILITY**



DESCRIPTION

Water-based paint composed of synthetic resins in aqueous dispersion, refined mineral fillers, special pigments and additives for easy application. Apply by brush, roller or spray for excellent coverage and a smooth interior finish. The dried coating has high whiteness, strong adhesion and good abrasion resistance. Hydrophobic additives provide resistance to dirt and ageing. Permeable to water vapour.

USE

For interior decoration in residential and commercial environments. Suitable for new cement substrates or repainting sound surfaces. On gypsum, plasterboard and particularly absorbent substrates, first apply an insulating primer such as PRIMER A 16. On old paint and powdery surfaces, first apply a consolidating primer such as PRIMER A 18.

SPECIFICATIONS

Paint interior cement and gypsum surfaces with an extra-white, water-repellent, breathable paint with high covering ability (such as PLATINUM by COLMEF S.r.l.). Apply by brush, roller or spray in at least two coats.

TECHNICAL DATA

Appearance	Thick paste
Colour	White
Specific weight (g/cm ³)	1.55
Solid residue	70%
Brookfield viscosity	20000 cP·s
Application temperature	+5°C to +35°C
Surface drying time	Around 30 min at +23°C
Waiting time between coats	2 hours
Ageing resistance	Excellent
Coverage per coat	9 - 10 m ² /litre

PACKAGING

14 litre bucket
33 buckets per pallet

4 litre bucket
64 buckets per pallet

Tests performed at 23°C and 50% R.H. in the absence of air ventilation.